



LED SUSPENSION LIGHT

019 018 0035





Technical Data	
Voltage (V)	110-240
Product Wattage	35
Equivalence with incandescentq lamp(W)	280
Colour Render Index (Ra)	>Ra80
Colour Temperature (K)	4000K
Materials	Iron + Aluminium + PC + Acrylic
Protection Class	I
Dimmable	No
EEI	A to A ⁺⁺
EEI Warm-up time up to 60 %of the full light output	A to A++
Warm-up time up to 60 %of the full light output	Instant Full Light
Warm-up time up to 60 %of the full light output Luminous Flux (Im)	Instant Full Light 2100
Warm-up time up to 60 %of the full light output Luminous Flux (Im) Luminous Efficacy (Im/W)	Instant Full Light 2100 60
Warm-up time up to 60 %of the full light output Luminous Flux (Im) Luminous Efficacy (Im/W) Rated Life (hrs)	Instant Full Light 2100 60 30.000


Applications

LED Suspension Light has been specifically designed for use indoors and is ideal for both hospitality and residential lighting.

Features

- \cdot High Lumen and CRI, Good quality & Constant Current driver.
- \cdot High heat dissipation, low carbon and environmental protection.
- $\cdot\,\mathsf{SMD}\,\mathsf{LED}\,\mathsf{Lamp}\,\mathsf{Base}$
- · Very low energy consumption

Technical Drawing



İstanbul Trakya Serbest Bölgesi Ferhatpaşa S.B. Mah. Açelya Sk. Dış Kapı: 2 İç Kapı: 301 Çatalca / İSTANBUL